

Double Braided Composite Rope

STRONGER THAN REGULAR DOUBLE BRAIDED WITH LESS STRETCH

FEATURES

- Made in U.S.A. to KENA Specifications.
- Double braided inner core with extra double braided outer jacket.
- Spliced eyes at both ends.
- Rot and mildew resistant.
- Recommended for cable pulling
- Durable and cost efficient



KENA CATALOG NO.	ROPE DIAMETER (inches/mm)	ROPE LENGTH (feet/meters)	AVERAGE TENSILE (lbs./kg)	WEIGHT PER REEL (lbs./kg)
CR58300	5/8 [15.9]	300 [91]	16,300 [7,394]	39.0 [17.7]
CR58600	5/8 [15.9]	600 [182]	16,300 [7,394]	78.0 [35.4]
CR58120	5/8 [15.9]	1,200 [365]	16,300 [7,394]	156.0 [70.8]
CR34300	3/4 [19.1]	300 [91]	23,500 [10,660]	53.0 [24.1]
CR34600	3/4 [19.1]	600 [182]	23,500 [10,660]	106.0 [48.1]
CR34120	3/4 [19.1]	1,200 [365]	23,500 [10,660]	212.0 [96.2]
CR78300	7/8 [22.3]	300 [91]	30,800 [13,970]	71.0 [32.2]
CR78600	7/8 [22.3]	600 [182]	30,800 [13,970]	142.0 [64.4]
CR78120	7/8 [22.3]	1,200 [365]	30,800 [13,970]	284.0 [128.8]

**ORDER FROM YOUR AUTHORIZED
KENA DISTRIBUTOR TODAY**

www.kenaindustries.com



Kena Industries, Inc.
COMMERCIAL DIVISION
P.O. Box 30037
Clarksville, TN 37040-0001
Phone: (800) 553-3380
Email: sales@kenaindustries.com